

Portable Conductivity/ Resistivity Meter

SC-110



Features:

- 💧 Light, handy, easy-to-use, IP65 water proof & low power consumption
- 💧 Auto self-test function, error code indication
- 💧 Large LCD display with temperature indication
- 💧 Auto-Read function
- 💧 Salinity and TDS correction function
- 💧 Temp. compensation: non-Linear compensation for resistivity or pure water measurement, Linear compensation for conductivity measurement
- 💧 Calibration can be set for cell constant manually or up to 5-point automatic recognition of standard solutions
- 💧 Temperature compensation with PT-1000 or NTC probe auto recognition
- 💧 Gradually continuous sample measurements average function to enhance stability
- 💧 Auto save the measurement with programmable time interval setting, min. 5 seconds
- 💧 Data-logger with memory for 450 data sets
- 💧 Built-in real time clock for auto power-off & data logger
- 💧 RS-232 interface for print or saved data transfer or time-interval measurement output



Portable Conductivity/ Resistivity Meter

SC-110

Specifications:

Model		SC-110
Measuring mode		Conductivity, Resistivity, Salinity, TDS, Temperature
Measuring range	Conductivity	0.00 μ S/cm~200.0mS/cm in 5 range for auto switch or manual switch
	Resistivity	0.00~100.00M Ω -cm
	Salinity	0.0~70.0ppt
	TDS	0~2000ppm
	Temperature	-10 $^{\circ}$ C~110 $^{\circ}$ C
Resolution & Accuracy	Conductivity	0.01 μ S/cm, \pm 0.5% (\pm 1digit)
	Resistivity	0.01M Ω -cm, \pm 1% (\pm 1digit)
	Salinity	0.1 ppt, \pm 0.5% (\pm 1digit)
	TDS	1 ppm, \pm 0.5% (\pm 1digit)
	Temperature	0.1 $^{\circ}$ C, \pm 0.2 $^{\circ}$ C (\pm 1digit)
Temperature Compensation		Automatic with PT-1000 or NTC 30K or manual adjustment
Temperature Coefficient		Non-Linear / 0.00~10.00% Linear
Reference Temperature		Tref 25 $^{\circ}$ C
Manual Calibration		Single point of known or cell constant calibration
Standard solution Calibration		Single or up to 5 points known standard solution calibration; default 5 standard solutions: 10 / 84 / 1413 μ S/cm & 12.88 / 100 mS/cm adjustable
Display		1/2" LCD display
RS-232 interface		Single way transfer the data to a computer or a printer
		Dual way by Modbus protocol
Data storage		Auto/Manual, 450 sets (measurement, temp., time, date, ID, number)
Power Supply		4 x AA Batteries
Battery Life		Around 350~1000 hours according to measuring range; auto-shut down within 10 mins. without operation
Dimensions		185mm x 98mm x 38mm
Weight		0.35kg
Protection		IP 65

*The specifications and appearance of the instrument are subject to change without notice.

Optional accessories:

- 4-electrode conductivity probe
- Resistivity probe C=0.01
- Resistivity probe C=0.05
- Connection cable 1.2M or 3M
- RS-232 connection cable
- Flexible electrode holder
- Flow chamber
- Plastic carrying case



SUNTEX INSTRUMENTS CO., LTD.

Web site: www.suntex.com.tw E-mail: suntex@ms1.hinet.net

13F., No.31, Lane 169, Kangning St., Xizhi Dist., New Taipei City 22180, Taiwan (R.O.C.)

Tel: 886-2-2695-9688 Fax: 886-2-2695-9693

Taichung Branch: 886-4-2319-7996 Kaohsiung Branch: 886-7-334-4103